

**Listing of Claims:**

Claims 1-29 (Canceled).

30. (Previously Presented) An interior member for a cab of a work vehicle, comprising:

a foundation body panel which has a first side and a second side, and which comprises a plurality of ribs at the second side,  
5 at least one space being defined by the ribs at the second side of the foundation body panel;

an outer layer material provided at the first side of the foundation body panel;

a sound absorbing member comprising a sound absorbing  
10 material provided between the outer layer material and the first side of the foundation body panel;

a metal plate provided at the second side of the foundation body panel, wherein the foundation body panel is fastened to the metal plate; and

15 a further sound absorbing member comprising a sound absorbing material provided on an opposite side of the metal plate with respect to the foundation body panel, such that the metal plate is provided between the further sound absorbing member and the foundation body panel;

20            wherein at least a plurality of the ribs of the foundation  
body panel cross each other.

Claims 31-34 (Canceled).

35. (Currently Amended) ~~The A~~ wall member ~~according to~~  
~~claim 34, further for a cab of a work vehicle,~~ comprising:

(i) an outer metal plate;

(ii) an interior member which is mounted to the outer metal  
5 plate, wherein the interior member comprises:

a foundation body panel which has a first side and a  
second side, and which comprises a plurality of ribs at the  
second side, at least one space being defined by the ribs at the  
second side of the foundation body panel, wherein the second side  
10 of the foundation body panel is mounted on the outer metal plate  
such that the outer metal plate closes the at least one space  
defined by the ribs;

an outer layer material provided at the first side of  
the foundation body panel;

15 a first sound absorbing member comprising a sound  
absorbing material provided between the outer layer material and  
the first side of the foundation body panel; and

a second sound absorbing member comprising a sound  
absorbing material filling at least one said space defined by the

20 ribs and closed by the outer metal plate at the second side of  
the foundation body panel; and

(iii) a first exterior layer provided on the outer metal  
plate on an opposite side of the metal plate with respect to the  
interior member, such that the outer metal plate is provided  
25 between the first exterior layer and the interior member.

36. (Previously Presented) The wall member according to  
claim 35, further comprising a second exterior layer provided on  
the first exterior layer, wherein the second exterior layer  
comprises one of a paint film and a resin layer that includes  
5 paint.

37. (Previously Presented) A wall member for a cab of a  
work vehicle, comprising:

(i) an outer metal plate; and

(ii) an interior member which is mounted to the outer metal  
5 plate, wherein the interior member comprises:

an inner metal plate, which is mounted on the outer  
metal plate with a space provided between the inner metal plate  
and the outer metal plate;

10 a foundation body panel which has a first side and a  
second side, and which comprises a plurality of ribs at the  
second side, at least one space being defined by the ribs at the

second side of the foundation body panel, wherein the second side of the foundation body panel is mounted on the inner metal plate such that the inner metal plate closes the at least one space defined by the ribs and such that the inner metal plate is positioned between the foundation body panel and the outer metal plate;

an outer layer material provided at the first side of the foundation body panel; and

a first sound absorbing member comprising a sound absorbing material provided between the outer layer material and the first side of the foundation body panel.

38. (Previously Presented) The wall member according to claim 37, further comprising a second sound absorbing member comprising a sound absorbing material provided in at least one said space defined by the ribs and closed by the inner metal plate at the second side of the foundation body panel.

39. (Previously Presented) The wall member according to claim 37, further comprising a further sound absorbing member comprising a sound absorbing material provided in the space between the inner metal plate and the outer metal plate.

Claims 40 and 41 (Canceled).